

KOMFORT EC DBE

Suspended heat recovery air handling units

• Heat exchanger type: Counter flow, Cross flow
• Heat exchanger material: Polystyrene, Enthalpy, Aluminum
• Sound-insulated casing
• Bypass: Auto
• BMS protocol: ModBus
• Casing material: Galvanized steel
• Humidity sensor: Optional
• CO2 sensor: Optional
• PM2.5 sensor: Optional

Lineup	Phases	Maximum airflow, m³/h	Service side	Control system	Reheater	Preheater	BMS protocol
KOMFORT EC DBE 300 R S21 DTV	1	340	Right	S21	Electric	Optional	ModBus
KOMFORT EC DBE 300 L S21 DTV	1	340	Left	S21	Electric	Optional	ModBus
KOMFORT EC DBE 300-E R S21 DTV	1	340	Right	S21	Electric	Optional	ModBus
KOMFORT EC DBE 300-E L S21 DTV	1	340	Left	S21	Electric	Optional	ModBus
KOMFORT EC DBE 550 R S21 DTV	1	608	Right	S21	Electric	Optional	ModBus
KOMFORT EC DBE 550 L S21 DTV	1	608	Left	S21	Electric	Optional	ModBus
KOMFORT EC DBE 550-E R S21 DTV	1	608	Right	S21	Electric	Optional	ModBus

 KOMFORT EC DBE 550-E L S21 DTV	1	608	Left	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900 R S21 DTV	1	1030	Right	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900 L S21 DTV	1	1030	Left	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900-E R S21 DTV	1	1030	Right	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 900-E L S21 DTV	1	1030	Left	S21	Electric	Optional	ModBus
 KOMFORT EC DBE 2000 S21 DTV	3	2100	Right	S21	Electric	✖	ModBus
 KOMFORT EC DBE 2000 S21	3	2100	Right	S21	Electric	✖	ModBus
 KOMFORT EC DBE 3000 S21 DTV	3	4300	Right	S21	Electric	✖	ModBus
 KOMFORT EC DBE 3000 S21	3	4300	Right	S21	Electric	✖	ModBus